

2024 EDITION

---

# AV SOLUTIONS **PRODUCT** OVERVIEW



---

PULSE**EIGHT**

---

## We are Pulse-Eight

For over a decade, our goal has been simple: to enhance our customer's experience by creating well designed, well manufactured and reliable products that use the latest innovative technology.

Our team of passionate engineering and manufacturing staff are experts in the technology we choose to work with. Specialists in HDMI®, HDBaseT® and AVoverIP, they ensure that all our products have been designed, built and tested to the very best standards.

# Contents

04	OneIP Video Over IP
08	18Gbps Video Matrix Solutions
12	Video Matrix Solutions
17	Video Matrix Comparison
18	ProAudio Audio Matrix Solutions
24	ProAmp Power Amplifier
26	HDMI Extender Sets
28	HDMI Splitters
30	Audio Accessories

OneIP

# VIDEO OVER IP

## CUTTING EDGE AV OVER IP TECHNOLOGY

**The result of four years of relentless innovation and development is here, a full duplex Video over IP transceiver.**

With our OneIP Transceiver, you get a true dual functionality device.

Unlike other transceivers on the market, OneIP can receive and transmit HDMI® sources at the same time, whilst still utilising a more cost effective, simpler to install, 1GbE infrastructure.

Unlock the full potential of your setup with support for the latest HDMI 2.0 18Gbps specification. Enjoy pristine 4K@60Hz 4:4:4, ensuring every detail is displayed with breath-taking clarity whilst maximising interoperability with video scaling for seamless integration with any display.



**18GBPS  
HDMI® 2.0**



**1GBE  
NETWORKING**



**FULL DUPLEX  
TRANSCIVER**



**5 YEAR  
WARRANTY**







# VIDEO OVER IP REDEFINED



one IP  
BY PULSEEIGHT

## VIDEO OVER IP TRANSCEIVER

**P8-ONEIP-1G-4K-TZ**

Our full-duplex transceiver enables both transmit and receive functions simultaneously. Coupled with the PurePlay receiver and transmitter products, the integrator has ultimate choice in system design.

### KEY FEATURES

- Full duplex transceiver
- HDMI 2.0 18Gbps specification
- Utilises 1Gb managed ethernet network
- Supports 10 & 12-bit HDR sources
- Visually lossless compression
- Ultra-low latency
- Source video scaling (up or down scaling)
- Supports all digital HDMI audio formats

HDBaseT

# 18Gbps MATRIX SOLUTIONS



DESIGNED TO  
MEET ALL YOUR  
VIDEO AND  
AUDIO NEEDS

The neo:X+ and neo:XSR represent the flagship of Pulse-Eight video distribution product. Each matrix supports 18Gbps HDMI® 2.0 resolutions up to and including 4K@60Hz 4:4:4 and we use HDBaseT's officially supported DSC technology to achieve remarkable picture quality.

With support for Dolby audio downmixing and ARC (audio return channel) amongst a host of other audio manipulation features. It all comes together to make the neo:X range a truly flexible and powerful partner in AV projects.



4K@60HZ 4:4:4




HDBaseT  
DIAGNOSTICS



CLOUD  
MONITORING



5 YEAR  
WARRANTY





HDBaseT

# 4K MATRIX SOLUTIONS



## KEY FEATURES

- Supports 4K@60Hz 4:4:4 UHD video
- Extend full 4K up to 100m
- Full, integrated audio matrix control
- HDBaseT diagnostics built-in
- CEC, IR or Web Remote Control
- Cloud monitoring

## 8X10 VIDEO MATRIX P8-HDBT-L-FFMN810A

## neoX+

### 8X10 VIDEO & AUDIO MATRIX P8-HDBT2-U-FFMJ1210

Our 18Gbps, 4K@60Hz 4:4:4, 8x10 Video Matrix with a full, integrated audio matrix.

The neo:X+ goes the distance, extend video up to 100 meters (330 feet). With audio breakout, Dolby Digital compliance and multiple video control methods.

- ARC (audio return channel)
- DSC visually lossless compression
- 5 Year warranty



## KEY FEATURES

- Supports 4K@60Hz 4:4:4 UHD video
- Extend full 4K up to 100m
- 6 audio breakouts
- HDBaseT diagnostics built-in
- CEC, IR or Web Remote Control
- Cloud monitoring

## neoXSR


### 6X6 VIDEO & AUDIO MATRIX P8-HDBT2-L-FFMJ66

The neo:XSR Video & Audio Matrix has it all - with multiple video inputs and both video and audio outputs. Featuring 6 HDMI® inputs, 4 HDBaseT outputs and 2 HDMI® outputs alongside 6 audio output zones (with the options of Optical and Digital Coax).

- ARC (audio return channel)
- DSC visually lossless compression
- 5 Year warranty

NEO:X+ 4K VIDEO MATRIX & PROAMP8

# CONCEPT WIRING GUIDE



- ### LEGEND
- Infrared
  - HDBaseT
  - Digital Audio
  - Analogue Audio
  - Ethernet
  - Speaker
  - HDMI®

## DRIVERS AVAILABLE FOR:

CRESTRON HOME ELAN RTI  
SAVANT Control4

HDBaseT

# MATRIX SOLUTIONS



## SIMPLE YET SOPHISTICATED VIDEO MATRIX SOLUTIONS

The award winning neo HDBaseT matrix range is the perfect blend of simplicity and sophistication, created by our passionate in-house engineering and production team for the sole purpose of seamlessly distributing video.

Designed with a core set of features to cover the majority of projects, the neo range represents unprecedented value. We recognise what's important to integrators, therefore we made sure our HDBaseT diagnostics and cloud monitoring are still included as standard.



4K@60HZ 4:2:0




HDBaseT  
DIAGNOSTICS



CLOUD  
MONITORING



5 YEAR  
WARRANTY





# HDBaseT MATRIX SOLUTIONS



## KEY FEATURES

- Supports 4K@60Hz 4:2:0 video
- Extend 4K up to 40m
- Extend 1080p up to 70m
- Source Audio Breakouts
- HDBaseT diagnostics built-in
- CEC, IR or Web Remote Control
- Cloud monitoring
- 5 Year warranty

neo:

## 8X10 VIDEO MATRIX

P8-HDBT-L-FFMN810A

The neo:8a is our flagship 4K 4:2:0 fixed format 8x10 HDBaseT matrix with added audio breakout.

The neo:8a can extend 4K up to 40 metres and 1080p up to 70 metres.

neo:

## 6X8 VIDEO MATRIX

P8-HDBT-L-FFMN68A

The neo:6a is our 6x8 matrix supporting 4K 4:2:0 with added HDMI audio breakout

The neo:8a can extend 4K up to 40 metres and 1080p up to 70 metres.



## KEY FEATURES

- Supports 4K@60Hz 4:2:0 video
- Extend 4K up to 40m
- Extend 1080p up to 70m
- Source Audio Breakouts
- HDBaseT diagnostics built-in
- CEC, IR or Web Remote Control
- Cloud monitoring
- 5 Year warranty



## KEY FEATURES

- Supports 4K@60Hz 4:2:0 video
- Extend 4K up to 40m
- Extend 1080p up to 70m
- Mirror HDMI outputs
- HDBaseT diagnostics built-in
- CEC, IR or Web Remote Control
- Cloud monitoring
- 5 Year warranty

neo:

## 4X4 VIDEO MATRIX

P8-HDBT-L-FFMS44-22

The neo:4 is our flagship 4x4 HDBaseT matrix with additional 2 mirrored HDMI ports.

## NEO:4 VIDEO MATRIX


# CONCEPT WIRING GUIDE

## DRIVERS AVAILABLE FOR:

CRESTRON HOME  
ELAN SAVANT RCI Control4


## LEGEND

- Infrared
- HDBaseT
- Digital Audio
- Analogue Audio
- Ethernet
- Speaker
- HDMI





CONCEPT WIRING GUIDE



LEGEND

- ..... Infrared
- ..... HDBaseT
- ..... Digital Audio
- ..... Analogue Audio
- ..... Ethernet
- ..... Speaker
- ..... HDMI®

DRIVERS AVAILABLE FOR:


CRESTRON HOME ELAN RTI SAVANT Control4

COMPARISON CHART

Product		neoX+	neo:XSR	neo:8a	neo:6a	neo:4
SKU		P8-HDBT2-U-FFMJ1210	P8-HDBT2-U-FFMJ66	P8-HDBT-L-FFMN810	P8-HDBT-L-FFMN68	P8-HDBT-L-FFMS44-22
Port Connections						
HDMI Inputs		8	6	8	6	4
Audio Inputs		4	-	-	-	-
HDBaseT Outputs		8	4	8	6	4
HDMI Outputs		2	2	2	2	2 (mirrored)
Audio Outputs		10	6	8	6	-
Video Resolutions						
*Denotes products that use Display Stream Compression (DSC) to compress 4K@60Hz 4:4:4 signals						
4K@60Hz 4:4:4		•*	•*			
4K@60Hz 4:2:2		•*	•*			
4K@60Hz 4:2:0		•	•	•	•	•
4K/HDR 10@60Hz		•*	•*			
4K/HDR 10@24Hz		•	•	•	•	•
1080p		•	•	•	•	•
720p		•	•	•	•	•
HDBaseT Video Distances						
4K	100 metres	•				
	40 metres	•	•	•	•	•
1080p	100 metres	•				
	70 metres	•	•	•	•	•
Features						
Ethernet Pass-through		10/100	-	-	-	-
IR Control		Bi-directional	Bi-directional	Bi-directional	Bi-directional	Bi-directional
HDMI-CEC Control		Yes	Yes	Yes	Yes	Yes
Web Interface		Yes	Yes	Yes	Yes	Yes
Cloud Monitoring		Yes	Yes	Yes	Yes	Yes
Automatic EDID		Yes	Yes	Yes	Yes	Yes
Third Party Control		Yes	Yes	Yes	Yes	Yes
HDMI ARC (Audio Return Channel)		Yes	Yes	-	-	-
PoH (Power over HDBaseT)		Yes	Yes	Yes	Yes	Yes
Maximum Pixel Clock		600Mhz	600Mhz	340Mhz	340Mhz	340Mhz
Maximum Bandwidth		18Gbps	18Gbps	10.2Gbps	10.2Gbps	10.2Gbps
Max Power Consumption		2Amps @ 240V				
Power Rating		100-240V 4.0/2.0A 50/60Hz				
Product Weight & Dimensions						
Product Weight		4.83kg	3.9kg	3.78kg	3.78kg	1.15kg
Height		13cm (3U)	8.9cm (2U)	9cm (2U)	9cm (2U)	4.3cm (1U)
Width		44cm	44cm	44cm	44cm	44cm
Depth		32cm	32cm	30.5cm	30.5cm	14cm

PROAUDIO

# DSP AUDIO MATRIX SOLUTIONS



## AUDIO DISTRIBUTION MADE SIMPLE

**Pulse-Eight’s ProAudio range of DSP capable pre-amp matrices offer innovative features and unmatched capabilities.**

Packed with features such as lip sync delay, 5 band DSP per zone, adjustable gain, zone locking, automatic audio conversion and third party control, our ProAudio range is unrivalled.


ProAudio has been designed for the custom install AV market, in many cases the need for an audio receiver can be eliminated by using the audio features of the ProAudio Series.

-  **FULL DSP**
-  **LIP SYNC CONTROL**
-  **THIRD PARTY CONTROL**
-  **5 YEAR WARRANTY**




PROAUDIO

# DSP AUDIO MATRIX



## KEY FEATURES

- 32 Stereo L/R Inputs
- 32 Digital Coax Inputs
- 16 Optical Inputs
- 64 Stereo L/R Outputs
- 64 Digital Coax Outputs
- 24 12V Triggers
- 1 Ethernet
- 1 RS232 Serial
- 5 Year warranty




## KEY FEATURES

- 32 Stereo L/R Inputs
- 32 Digital Coax Inputs
- 16 Optical Inputs
- 48 Stereo L/R Outputs
- 48 Digital Coax Outputs
- 18 12V Triggers
- 1 Ethernet
- 1 RS232 Serial
- 5 Year warranty

## ProAudio3264

DSP AUDIO MATRIX

P8-PROAUDIO3264



## KEY FEATURES

- 32 Stereo L/R Inputs
- 32 Digital Coax Inputs
- 16 Optical Inputs
- 32 Stereo L/R Outputs
- 32 Digital Coax Outputs
- 12 12V Triggers
- 1 Ethernet
- 1 RS232 Serial
- 5 Year warranty

## ProAudio32

DSP AUDIO MATRIX

P8-PROAUDIO32



## KEY FEATURES

- 16 Stereo L/R Inputs
- 16 Digital Coax Inputs
- 8 Optical Inputs
- 32 Stereo L/R Outputs
- 32 Digital Coax Outputs
- 12 12V Triggers
- 1 Ethernet
- 1 RS232 Serial
- 5 Year warranty

## ProAudio1632

DSP AUDIO MATRIX

P8-PROAUDIO1632



## KEY FEATURES

- 16 Stereo L/R Inputs
- 16 Digital Coax Inputs
- 8 Optical Inputs
- 8 CAT5e (Remote Source) Inputs
- 32 Stereo L/R Outputs
- 32 Digital Coax Outputs
- 1 Ethernet
- 1 RS232 Serial
- 5 Year warranty

## ProAudio16RS


DSP AUDIO MATRIX

P8-PROAUDIO16RS



PROAUDIO

DSP AUDIO MATRIX



KEY FEATURES

- 16 Stereo L/R Inputs
  - 16 Digital Coax Inputs
  - 16 Optical Inputs
  - 16 Stereo L/R Outputs
  - 16 Digital Coax Outputs
  - 1 Ethernet
- 1 RS232 Serial
  - 5 Year warranty



KEY FEATURES

- 8 Stereo L/R Inputs
  - 8 Digital Coax Inputs
  - 8 Optical Inputs
  - 8 Stereo L/R Outputs
  - 8 Digital Coax Outputs
  - 1 Ethernet
- 1 RS232 Serial
  - 5 Year warranty

ProAudio16

DSP AUDIO MATRIX  
P8-PROAUDIO16

48 AUDIO INPUTS

16 AUDIO OUTPUTS

THIRD PARTY CONTROL

ProAudio8

DSP AUDIO MATRIX  
P8-PROAUDIO8


24 AUDIO INPUTS

8 AUDIO OUTPUTS

THIRD PARTY CONTROL

PROAMP8, PROAUDIO1632 & NEO:X+ VIDEO MATRIX

CONCEPT WIRING GUIDE



LEGEND

Infrared

HDBaseT

Digital Audio

Analogue Audio

Ethernet

Speaker

HDMI®

DRIVERS AVAILABLE FOR:

CRESTRON

ELAN

RTI

SAVANT

Control4



# PROAMP AMPLIFIER



# ALL IN ONE SOLUTION FOR AMPLIFICATION

## ProAmp8

P8-PROAMP8



- 8 ANALOGUE INPUTS
- 1 DOLBY INPUT
- 8 AUDIO OUTPUT ZONES
- 200W @4Ω BRIDGE MODE
- 100W @4Ω 50W @8Ω
- THIRD PARTY CONTROL
- CLOUD MONITORING

Pulse-Eight's ProAmp8 is a powerful and versatile 8-Zone Power Amplifier that offers a wide range of features, such as; full audio DSP and EQ settings, Multi-Zone Mode and Dolby Digital Surround Sound Modes. The ProAmp8 is the perfect partner to Pulse-Eight's ProAudio range and our latest neo:X matrices.

### KEY FEATURES

- 100 watts per channel
- 8 Stereo (L/R) analogue inputs
- 1 digital input with Dolby support
- 8 Stereo phoenix connector outputs
- Bridgeable output zones
- Full Dolby Zone DSP and Equaliser (EQ) control
- Fault detection and system reset
- Low-energy consumption
- "Automatic sensing" and 12V Trigger options
- User-friendly WebUI control

# NEO HDMI® EXTENDERS

- PoH** PoH AS STANDARD
- LOW PROFILE**
- 3 YEAR WARRANTY**



## HDMI EXTENSION WITH A DIFFERENCE

Our neo range of HDMI® over HDBaseT™ extender sets offer the very best in performance and flexibility.

With the aim to keep our HDMI® extension solutions simple, instead of hundreds of variants, we've created simple tiers, each more capable than the last. Features include bi-directional IR, PoH, DSC, CEC, RS232 and ARC, depending on model.



### neo:Ultra HDMI® EXTENDER SET P8-HDBT2-U-EXSET

- 4K** EXTEND 4K UP TO 100M
- HD** EXTEND 1080P UP TO 100M
- HDMI® AUDIO RETURN**
- 18GBPS 4K**

#### KEY FEATURES

- Supports 4K@60Hz 4:4:4
- Extend 4K and 1080p up to 100m
- An ultra thin 13mm depth enclosure
- Wall Mountable
- ARC (Audio Return Channel)
- Bi-Directional Infra-Red
- Ethernet 10/100 Connection
- Serial RS232 via 3.5mm
- HDCP 2.2 Compliant



### neo:Pro HDMI® EXTENDER SET P8-HDBT2-P-EXSET

- 4K** EXTEND 4K UP TO 70M
- HD** EXTEND 1080P UP TO 100M
- HDMI® AUDIO RETURN**
- 4K@60HZ 4:2:0**

#### KEY FEATURES

- Supports 4K@60Hz 4:2:0
- Extend 4K to 70m and 1080p to 100m
- An ultra thin 13mm depth enclosure
- Wall Mountable
- ARC (Audio Return Channel)
- Bi-Directional Infra-Red
- Ethernet 10/100 Connection
- Serial RS232 via 3.5mm
- HDCP 2.2 Compliant



### neo:lite HDMI® EXTENDER SET P8-HDBT-L-EXSET

- 4K** EXTEND 4K UP TO 40M
- HD** EXTEND 1080P UP TO 70M
- 4K@60HZ 4:2:0**

#### KEY FEATURES

- Supports 4K@60Hz 4:2:0
- Extend 4K to 40m
- Extend 1080p to 70m
- Wall Mountable
- Low Power
- Bi-Directional Infra-Red
- PoH Receiver
- HDCP Compliant



# HDMI® SPLITTER SOLUTIONS

- PoH** PoH AS STANDARD
- LOW PROFILE**
- 3 YEAR WARRANTY\***

Whether you need to split a source device over long distances with HDBaseT, or more locally with HDMI®, Pulse-Eight has a compact range to help.

Our TechTools 1x2 HDMI® splitter with inbuilt downscaler also acts as a HDMI® troubleshooter. Something every integrator should have one of on the van for those occasions HDMI® needs a little bit of help.

\*The neo:1x4 Splitters come with 3 year warranty and the Tech Tools has a 1 year warranty.



- HDMI** 1 HDMI® INPUT
- HDBT** 4 HDBASET OUTPUTS
- 4K@60Hz 4:2:0**
- 4K** EXTEND 4K UP TO 40M
- CLOUD MONITORING**

## KEY FEATURES

- Supports 4K@60Hz 4:2:0
- Extend 4K up to 40m
- Extend 1080p up to 70m
- HDBaseT diagnostics built-in
- Responsive Web Interface
- Cloud monitoring
- PoH (Power over HDBaseT)
- Rack mountable
- 3 Year warranty

## neo: 1-4 HDBaseT™ SPLITTER P8-HDBT-L-SP4

Our neo HDBaseT™ splitter can extend 4K up to 40 meters and 1080p up to 70 metres, with CEC control and IR control.



- HDMI** 1 HDMI® INPUT
- HDMI** 4 HDMI® OUTPUTS
- 4K@60Hz 4:4:4**
- CLOUD MONITORING**

## KEY FEATURES

- Supports 4K@60Hz 4:4:4
- Responsive Web Interface
- Cloud monitoring
- Return IR Control
- CEC Control
- Automatic EDID Management
- Rack mountable
- 3 Year warranty

## neo: 1-4 HDMI® SPLITTER P8-HDMI2-SP4

With one HDMI® source, you can easily distribute to four simultaneous HDMI® outputs plus access to our exclusive Cloud Monitoring Portal.



- HDMI** 1 HDMI® INPUT
- HDMI** 2 HDMI® OUTPUTS
- 4K@60Hz 4:4:4**
- DOWNSCALING**

## KEY FEATURES

- Supports 4K@60Hz 4:4:4
- 4K>1080p Downscaler function
- Return IR Control
- Audio Extraction
- Automatic EDID Management
- 1 Year warranty

## TECH TOOLS 1-2 HDMI® SPLITTER P8-HDMI2-SP2-DS

Our 1-2 Splitter with built-in downscaler that enables the distribution of a single 4K source signal to 2 HDMI® display devices simultaneously.

## OUR SIMPLE SOLUTIONS FOR SENDING HDMI TO MULTIPLE DISPLAYS

## ACCESSORIES

# AUDIO SOLUTIONS

## AUDIO SOLUTIONS FOR EVERY REQUIREMENT



Modern day installations require innovative solutions and can often push the envelope of what consumer audio and video devices were designed to do. Working closely with installers, we've developed a range of products that provide simple fixes for better integration of complex audio and video distribution systems.

All our accessories come with 3 years warranty and are designed to work seamlessly alongside our matrices and extenders, but also work standalone if required.

### DIGITAL AUDIO OVER CAT5E/6 EXTENDER

#### P8-AE-CAT-EXSET

Digital audio over extreme distances can be tricky in isolation, our audio extender uses a standard CAT cable to seamlessly transmit S/PDIF (Toslink) audio over 200m.



#### KEY FEATURES

- Extends audio via a single CAT cable
- Supports 2ch PCM audio inputs
- Compact design
- Supports coaxial or S/PDIF signals
- 5.1 Compressed audio supported
- 3 Year warranty
- Stereo and Multichannel digital audio
- Extension length up to 200m

### AUDIO DELAY DEVICE

#### P8-AD340

The perfect solution to lip sync problem with ~20 millisecond increments from its 16-way selector you can delay the audio from 20-340ms. Delay stereo audio with a simple L/R phono input and output connection.

#### KEY FEATURES

- The perfect solution to lip sync issues
- Simple L/R phono input and output connections
- Compact design
- 20 millisecond increments from the 16-way selector
- Delay the audio from 20-340ms
- 3 Year warranty



### DOLBY® DIGITAL DOWNMIXER DAC (DIGITAL TO ANALOGUE CONVERTER)

#### P8-DDAC

With our digital to analogue audio converter, audio setups are capable of decoding connected S/PDIF coaxial or TOSLINK optical digital audio sources to standard analogue stereo (L/R) audio.

#### KEY FEATURES

- Inputs for coaxial and optical
- Analogue stereo (L/R) output
- Compact design
- Ensures a reliable transition from modern digital sources
- Decodes connected S/PDIF coaxial or TOSLINK optical digital audio sources
- 3 Year warranty



### HDMI® DOWNMIXER DAC (DIGITAL TO ANALOGUE CONVERTER)

#### P8-HDMIDAC

The HDMI® DAC video scaler and digital to audio converter (DAC) is designed to be placed between a display and a source device. It adjusts resolution and audio from an incoming HDMI source and scales the output to a level compatible with its display capabilities.

#### KEY FEATURES

- Supports 4K and 1080p
- 3.5mm audio breakout
- Compact design
- In line downmix of Dolby Digital to stereo PCM over HDMI®
- Downscale 4K/30p > 1080/24p
- 3 Year warranty
- Upscale 1080/24p > 4K/30p,







**HEAD OFFICE:**

Pulse-Eight Limited  
8-12 Alder Hills, Poole,  
Dorset, BH12 4AL, UK

+44 (0)1202 413610

[sales@pulse-eight.com](mailto:sales@pulse-eight.com)

[WWW.PULSE-EIGHT.COM](http://WWW.PULSE-EIGHT.COM)